

ROCK POWER - MICROBIAL

MICROBIAL REMEDIATOR / CLEANER

DESCRIPTION:

ROCK POWER- MICROBIAL is a fast, economical and natural oil-contaminate remover. Activated MICROBES in a specially designed liquid suspension penetrate concrete and completely digest oil contamination, converting it into carbon dioxide and water, naturally occurring by-products. THIS PRODUCT IS ENVIRONMENTALLY SAFE FOR HUMANS, PETS, PLANTS, AND AQUATIC LIFE.

USES:

ROCK POWER-MICROBIAL is designed for the remediation of any and all oil-based contaminants (including oils, fats, fuels, grease, etc.) from floors, driveways, and anywhere oil contamination is a problem, available in two grades:

SURFACE

hydrocarbons/petroleum-based oils

or

FOOD-GRADE

lipid-based fats/proteins (grease, cellulose, starch)

TYPICAL COVERAGE:

Depends on the size and contamination level of the surface.

ADVANTAGES:

- Cleans without polluting
- No storage/shipping regulations
- Will not harm hands or skin
- Non-flammable/non-hazardous
- NO VOC's
- Can be used on any surface
- Leave no residue behind
- Minimizes number of cleaners needed

TYPICAL PROPERTIES:

APPLICATION PROPERTIES	
Volume mix ratio	N/A (already mixed)
VOC	0 g/l (EPA method 24)
Application Temps.	40° - 100° F
Shelf Life	1 Year+ in unopened containers
Shelf Life (activated)	90 - 120 days

PACKAGING:

- 1 Gallon unit (activated)
- 5 Gallon unit (activated)
- 55 Gallon drum + microbe packets

ROCK POWER-MICROBIAL

LIMITATIONS & FOR BEST RESULTS:

- Ambient and substrate temperatures much be kept between 40 & 100. In excess cold, the microbes become dormant. In excess heat, the microbes will die.
- The microbes must have water to live and work. Without water, they will go dormant until water (and “food”) is available.
- Microbes cannot survive excessive amounts of bleach of bactericide.

PRODUCT APPLICATION:

1. This product may be applied with either a spray or a brush. The affected area must be agitated with a brush, manually or with a power scrubber. (This is determined by the size of the area to be cleaned.)
2. The solution must not rise above 120 F, and must not dry out. Water must be present at all times.
3. Cleaned area may be rinsed off after approx. 20 minutes. The complete remediation process continues for several days.
4. After application, the solution can be collected, stored in containers, and re-used several times.

PRODUCT STORAGE:

DO NOT subject this product to temperatures below 40 F, and in excess of 120 F. Used solution is non-flammable, and may be stored in open containers.

CLEAN UP /DISPOSAL:

This product, activated or not, contains no hazardous materials, and may be simply rinsed away. All components and by-products are biodegradable. When properly rinsed this product leaves no residue

IMPORTANT NOTICE:

Always read and acquaint yourself with ROCK-TRED'S Product Data Sheet, MSDS [material safety data sheet], and product labels for each individual product prior to mixing and prior to use.

For further assistance, product questions, additional information and/or unexpected or unusual installation conditions – contact your local representative or ROCK-TRED directly for recommendations.

WARRANTY:

Information about ROCK-TRED products is given, to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you make your own tests to determine suitability of the product for the particular purpose. As products are often applied or used under conditions beyond our control, ROCK-TRED cannot guarantee anything except the quality of its products. ROCK-TRED warrants that the products meet the specifications set forth by ROCK-TRED, but we reserve the right to change any given specification prior to notice. ROCK-TRED DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of a ROCK-TRED product constitutes acceptance of the terms of this limited warranty and the terms and conditions set out in our invoice, contrary provisions of buyer's purchase documents notwithstanding. Upon receipt of the merchandise, purchaser has 30 days to notify ROCK-TRED, in writing, that materials are defective. In the event ROCK-TRED finds that the product delivered is off specification, ROCK-TRED will, at its sole discretion, either replace the product(s) or refund the purchase price thereof, and ROCK-TRED's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of ROCK-TRED exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. ROCK-TRED will, under no circumstances, be liable for special, incidental, or consequential damages. This warranty supersedes all other guaranties, whether oral or written, and whether expressed, implied, or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals that may cause serious physical injury. Before using, please read the Material Safety Data Sheet and follow all precautions to prevent bodily harm.