



# ROCK-POWER®

## Concentrated Liquid Floor Cleaner and Concrete Neutralizer

### DESCRIPTION:

ROCK-POWER Liquid Floor Cleaner and Concrete Neutralizer is a powerful cleaner and degreaser. It is safe, odorless, clear, non-flammable and does not contain ammonia or bleach. ROCK-POWER's unique combination of water softeners and extra strength detergents provides a powerful product that can be used concentrated (as is) or diluted up to 32:1 with hot, cold, hard or soft water.

### RECOMMENDED USES:

ROCK-POWER is an effective way of cleaning all washable surfaces, including concrete floors (bare or sealed), all types of metal, brick, marble, rubber, formica, linoleum, vinyl, woodwork and porcelain. ROCK-POWER is capable of cleaning a wide range of tough dirt and stains, including: heavy industrial grease and grime, oils, resins, spilled chemicals, food and beverage spills, mildew, water stains and heel marks.

### FEATURES:

- Excellent Cleaning Capabilities
- NSF Approved
- Water Based
- Odorless
- Water Dilutable
- Can Be Used With Industrial Cleaning Equipment
- Economical
- Environmentally Friendly
- Safe
- Easy To Use
- Non-Abrasive
- Non-Flammable
- Colorless
- Non-Irritating
- Shelf Life – 2 Years

### PACKAGING:

- 1 gallon (3.8 L) F-Style container
- 5 Gallon (19 L) Pail
- 55 Gallon (208 L) Drum

### USAGE RATIOS:



Surface To Clean	ROCK-POWER:WATER Dilution Ratio
Sealed or Coated Floors	4 oz (118 ml): 1 gal (3.8 L)
Ceramic Tile or Masonry	8 oz (237 ml): 1 gal (3.8 L)
Concrete Spot Cleaning	1 qt (.946 L): 1 gal (3.8 L)
Ovens and Grills	1 pint (.5 qt) : 1 gal (3.8 L)
Trucks, Autos, Metal	4 oz (118 ml) : 1 gal (3.8 L)
Parts (Dip Tanks)	Full Strength
Glass	1 oz (29.6 ml): 1 gal (3.8 L)
Vinyl, Linoleum	1 oz (29.6 ml) : 1 gal (3.8 L)

### FOR BEST RESULTS:

- DO NOT Allow Solution To Dry (MUST Be Rinsed).
- Thoroughly Mix Contents of Container Before Use.
- Rinse Surface Thoroughly After Each Use.

**Review ROCK-TRED'S Material Safety Data Sheets (MSDS) for this product prior to mixing and applying. In addition, thoroughly review the Data Sheet and product labels.** Por favor, póngase en contacto con ROCK-TRED Corporation al núm. telefónico 1800-762-8733 para la Hoja de Datos de Material y la Hoja de Datos de Seguridad (MSDS) en español. (Deje su núm. de teléfono).

**MIXING:**

Thoroughly mix container before each use by shaking or otherwise agitating.

**APPLICATION:**

ROCK-POWER can be applied by using automatic floor scrubbers, pressure washers, dip tanks, mops, spray bottles or rags. ROCK-POWER can be diluted with water for most applications (see chart).

For unprotected floors that are heavily soiled, let solution stand several minutes before rinsing and/or increase the concentration.

**For sealed or coated floors**, refer to the dilution ratio on the front page and use either a walk-behind or riding power scrubber to clean the floor surface.

**For ceramic tile and masonry**, apply the recommended ROCK-POWER solution with a brush paying special attention to the embedded dirt in the grout. Let stand for 15 minutes before rinsing. For fireplaces, spray-apply the solution, scrub lightly and rinse.

**For concrete spot cleaning**, brush the recommended solution onto surface lightly. The ratio prescribed for this type of application is effective in removing wax, thin acrylic sealers, oil and grease. Let the solution sit until contaminates dissolve and follow up with a rinse of heavily diluted ROCK-POWER.

**For ovens and grills**, spray apply the appropriate ROCK-POWER solution, let stand for approximately 15 minutes and thoroughly rinse with water. A light scrubbing may be necessary.

**For car cleaning**, the use of a pressure washer will yield the best results. Just use the dilution ratio described on the front page and perform cleaning in the same fashion as with any other detergent. Rinse thoroughly when

completed.

**For use in parts dip tanks**, use ROCK-POWER undiluted. At full strength, the product is excellent for cleaning and degreasing machinery, and it brightens engine parts as well. Follow up with a mild solution for rinsing.

**For glass cleaning**, spray-apply the recommended solution and wipe with a damp cloth.

**For vinyl flooring or furniture**, use either a spray application or a mop and clean as you would normally with any other cleaning agent. For furniture, wipe with damp cloth afterwards. For floors, mop a second time with straight water as a rinsing.

**CLEAN UP:**

Application equipment should be cleaned using soap and water.

**DISPOSAL:**

Empty containers may contain product residue, including flammable or combustible vapors. Do not cut, puncture or weld near these containers. Label warnings must be observed until containers have been commercially cleaned or reconditioned. Containers to be thrown out must be disposed in accordance with federal, state and local regulations. Use only licensed hazardous waste disposal companies.

**MAINTENANCE:**

For optimal floor appearance and performance following installation, refer to ROCK-TRED's Floor Maintenance Instructions.

**CUSTOMER NOTE:**

For information on application situations not covered above, contact your local ROCK-TRED representative or the corporate office at 847-673-8200.

**WARRANTY STATEMENT:**

Information about ROCK-TRED products is given to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you will make your own tests to determine the suitability of the product for your particular purpose. As products are often applied or used under conditions beyond our control, ROCK-TRED cannot guarantee anything but the quality of its products. ROCK-TRED warrants that its products meet the specifications set forth by ROCK-TRED, but we reserve the right to change any given specification without prior notice. ROCK-TRED DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of ROCK-TRED products constitutes acceptance of the terms of this limited warranty and the terms and the conditions set out in our invoice, contrary provisions of buyer's purchase documents notwithstanding. Upon receipt of merchandise, purchaser has 30 days to notify ROCK-TRED in writing that materials are defective. In the event ROCK-TRED finds that the product delivered is off specification, ROCK-TRED will, at its sole discretion, either replace the product or refund the purchase price thereof, and ROCK-TRED's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of ROCK-TRED exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. ROCK-TRED will under no circumstances be liable for special, incidental or consequential damages. This warranty supercedes all other guaranties, whether oral or written, and whether expressed, implied or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals which may cause serious physical injury. Before using, please read the Material Safety Data Sheet and follow all precautions to prevent bodily harm.

ROCK-POWER DS REV: 11/7/03



Manufacturing and Headquarters: 3415 Howard St., Skokie, IL 60076-4032 U.S.A.

(800) ROC-TRED • (800) 762-8733 • (847) 673-8200 • FAX (847) 679-6665

[www.rocktred.com](http://www.rocktred.com)