



ROCK-TRED® Colorants

Color Dispersion for Use in Field for Pigmentation of ROCK-TRED Coatings and Resurfacers

DESCRIPTION:

ROCK-TRED Colorants are concentrated color additives. Available in 21 standard colors for addition to ROCK-TRED clear and color base formulations.

RECOMMENDED USES:

ROCK-TRED Colorants are used for field pigmentation of ROCK-TRED coatings and resurfacer systems.

FEATURES:

- Virtually Universal Formulation
- Low Odor
- VOC Compliant in All Areas
- Mixes Easily into Rock-Tred Products
- Stable Formula
- Allows for Fast Response to Customer Color Requirements
- Reduces Inventory Requirements

FOR BEST RESULTS:

- Consult each Product's Data Sheet to Ensure Compatibility
- When in doubt that the proper hiding properties will be obtained for a specific project, perform a test patch first.
- Use of more than recommended levels of ROCK-TRED Colorant may result in extended cure times, lower physical properties or chemical resistance.
- Pre-mix each container of Colorant before using.
- On large installations, make sure all colorants are from the same batch, or combine multiple batch lots to ensure uniformity of color.
- Do NOT thin ROCK-TRED Colorants

PACKAGING:

- ROCK-TRED Colorants are packaged in quart (32 oz) (.95 L) containers and shipped four to a carton.

STANDARD ROCK-TRED COLORANT COLORS



- Colors that may require additional coats or increased loading for proper hiding

THESE IMAGES ARE REPRESENTATIVE OF THE STANDARD COLORS OF THE ROCK-TRED COLORANT SYSTEM. ALL COLORS SHOWN ARE APPROXIMATIONS MADE AS ACCURATELY AS POSSIBLE AND MAY VARY DUE TO FINISH, TEXTURE AND THE ROCK-TRED COATING AND RESURFACER PRODUCT SELECTED. PLEASE NOTE THAT COLORS WILL CHANGE DEPENDING ON THE PRODUCT THE COLORANT IS USED IN. COLORS MAY VARY FROM BATCH TO BATCH. FACTORY PIGMENTED VERSIONS OF ROCK-TRED PRODUCTS ARE AVAILABLE IN THE ABOVE COLORS FOR LARGER ORDERS. WHERE COLOR MATCHING IS CRITICAL, USE THE SAME BATCH CODE AND A SAMPLE COLOR CHIP SHOULD BE REQUESTED. IN CRITICAL INSTALLATIONS, AN APPLIED SAMPLE IS RECOMMENDED. CUSTOM COLORS AVAILABLE UPON REQUEST FOR AN ADDITIONAL COST.

Property	Typical Value
Shelf Life	2 Years
Mixing Ratio:	See chart on reverse side
Wt/Gal (lbs./gal)	Varies from 9.6 to 16.5 (1.12 – 1.98 kg/L)
Packaging	Quarts; Four per carton
% Solids by Volume	17%-74%, varies
Flash Point	>200°F (93°C)

Based upon a seven day cure at 75°F (24°C)

Color	Product No.	Water-Based Epoxies (per 3 gallons)	100% Solids Epoxies (per 3 gallons)	CHEM-THANE Urethanes* (per 3 gallons)	POXI-ROCK Flooring Neutral (per 35.5# bag of aggregate)
002 Heavenly White	11602	2-Quarts (1.9L)	2-Quarts (1.9L)	2-Quarts (1.9L)	3 ounces (.09 L)
*003 Midnight Black	11603	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
004 Canary Yellow	11604	2-Quarts (1.9L)	2-Quarts (1.9L)	2-Quarts (1.9L)	5 ounces (.15 L)
*005 Fire Engine Red	11605	2-Quarts (1.9L)	2-Quarts (1.9L)	2-Quarts (1.9L)	5 ounces (.15 L)
006 Lt. Gray	11606	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
007 Thunder Gray	11607	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
008 Battleship Gray	11608	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
009 Charcoal Gray	11609	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
010 Tile Red	11610	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
011 Pistachio Green	11611	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
*012 Hunter Green	11612	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
013 Caribbean Blue	11613	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
014 Ocean Blue	11614	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
*015 Oxford Blue	11615	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
016 Sandstone	11616	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
017 Cement Beige	11617	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
018 Cocoa Brown	11618	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
029 Safari Tan	11629	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
*030 Safety Orange	11630	2-Quarts (1.9L)	2-Quarts (1.9L)	2-Quarts (1.9L)	5 ounces (.15 L)
031 Steel Gray	11631	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)
032 Light Mint Green	11632	1-Quart (.95L)	1-Quart (.95L)	1-Quart (.95L)	3 ounces (.09 L)

Review ROCK-TRED'S Material Safety Data Sheets (MSDS) for this product prior to mixing and applying. In addition, thoroughly review the Data Sheet and product labels. Por favor, póngase en contacto con ROCK-TRED Corporation al núm. telefónico 1800-762-8733 para la Hoja de Datos del Material y la Hoja de Datos de Seguridad (MSDS) en español. (Deje su núm. de teléfono).

MIXING:

Each container of ROCK-TRED Colorant must be pre-mixed before using. On larger installations, to ensure uniformity of color, combine multiple batch lots together. The specified quantity of ROCK-TRED Colorant is then added to the Resin portion and thoroughly blended for a minimum of 1 minute with a spiral mixing blade (available from ROCK-TRED) that is attached to a low-speed (400-600 RPM) electric drill. Take care not to induce air into the material when mixing. Then the container of Hardener is added and mixed per the instructions for that product.

CLEAN UP:

Application equipment should be cleaned using soap and water or solvent where necessary. Roller covers should be discarded after use.

WARRANTY STATEMENT:

Information about ROCK-TRED products is given to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you will make your own tests to determine the suitability of the product for your particular purpose. As products are often applied or used under conditions beyond our control, ROCK-TRED cannot guarantee anything but the quality of its products. ROCK-TRED warrants that its products meet the specifications set forth by ROCK-TRED, but we reserve the right to change any given specification without prior notice. ROCK-TRED DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of ROCK-TRED products constitutes acceptance of the terms of this limited warranty and the terms and the conditions set out in our invoice, contrary provisions of buyer's purchase documents notwithstanding. Upon receipt of merchandise, purchaser has 30 days to notify ROCK-TRED in writing that materials are defective. In the event ROCK-TRED finds that the product delivered is off specification, ROCK-TRED will, at its sole discretion, either replace the product or refund the purchase price thereof, and ROCK-TRED's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of ROCK-TRED exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. ROCK-TRED will under no circumstances be liable for special, incidental or consequential damages. This warranty supercedes all other guaranties, whether oral or written, and whether expressed, implied or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals which may cause serious physical injury. Before using, please read the Material Safety Data Sheet and follow all precautions to prevent bodily harm.

ROCK-TRED Colorants DS 3/03



Manufacturing and Headquarters: 3415 Howard St., Skokie, IL 60076-4032 U.S.A.
 (800) ROC-TRED • (800) 762-8733 • (847) 673-8200 • FAX (847) 679-6665
www.rocktred.com

DISPOSAL:

Empty containers may contain product residue, including flammable or combustible vapors. Do not cut, puncture or weld near these containers. Label warnings must be observed until containers have been commercially cleaned or reconditioned. Containers to be thrown out must be disposed in accordance with federal, state and local regulations. Use only licensed hazardous waste disposal companies.

MAINTENANCE:

For optimal floor appearance and performance following installation, refer to ROCK-TRED's Floor Maintenance Instructions.

CUSTOMER NOTE:

For information on application situations not covered above, contact your local ROCK-TRED representative or the corporate office at 1-847-673-8200.