



### DESCRIPTION:

THIXO™ is a powder additive used for thickening 100% solids epoxy coatings. Thixo is non-reactive and easy to use as a stir in additive at the job site.

### RECOMMENDED USES:

Thixo can be added to 100% solids epoxy coatings to achieve an "orange peel" effect in the finished coating. Adding more Thixo to a coating creates a paste like mixture that can be used to fill small cracks and holes in spalled concrete.

THIXO can be used with the following ROCK-TRED Products:

CHEM-ROCK® Seal/Coat  
CHEM-ROCK® LT-Seal/Coat  
ECONO-POXI™  
NOVO-POXI®  
NOVO-POXI® LT  
ELASTI-POXI® Joint Fill  
ELASTI-POXI® Membrane

### FEATURES:

- Increases Coating Viscosity
- Non-reactive
- Easy To Use
- Economical
- Enables Smooth Patching
- Can Provide Heavy "Orange Peel"
- Environmentally Friendly

### PACKAGING:

- 25 lb. Pail
- 200 lb. Drum

### FOR BEST RESULTS:

- Add THIXO Slowly While Mixing.
- Keep Dry.
- Make Sure THIXO is Completely Mixed In.

**Review ROCK-TRED'S Material Safety Data Sheets (MSDS) for this product prior to mixing and applying. In addition, thoroughly review the Data Sheet and product labels.**

Por favor, póngase en contacto con ROCK-TRED Corporation al núm. telefónico 1800-762-8733 para la Hoja de Datos del Material y la Hoja de Datos de Seguridad (MSDS) en español. (Deje su núm. de teléfono).

### MIXING AND APPLICATION:

**To create an aggressive "orange peel" effect**, add up to 1 gallon (3.8 L) of THIXO (about 6 lbs) per 3 gallons (11.4 L) of 100% solids epoxy. Premix the Hardener and Resin in accordance with the mixing instructions of that product. Immediately start adding the THIXO slowly while mixing until the desired consistency is attained. Apply the coating following standard application directions. The coating will be thicker and will also cure more slowly after the THIXO has been added. A natural "orange peel" effect will result.

**For filling fine cracks and holes in spalled concrete**, add up to 2 gallons (7.6 L) of THIXO (about 12 lbs) per 3 gallons (11.4 L) of mixed 100% solids epoxy. Follow mixing instructions outlined above. The final mixture should have the consistency of a thick paste. This paste can be trowel applied to fine cracks and small holes in the concrete. Fill any depressions in the concrete and strike off to level with a steel trowel.

**CLEAN UP:**

Application equipment should be cleaned using soap and water.

**DISPOSAL:**

Empty containers may contain product residue, including flammable or combustible vapors. Do not cut, puncture or weld near these containers. Label warnings must be observed until containers have been commercially cleaned or reconditioned. Containers to be thrown out must be disposed in accordance with federal, state and local

regulations. Use only licensed hazardous waste disposal companies.

**MAINTENANCE:**

For optimal floor appearance and performance following installation, refer to ROCK-TRED's Floor Maintenance Instructions.

**CUSTOMER NOTE:**

For information on application situations not covered above, contact your local ROCK-TRED representative or the corporate office at 847-673-8200.

---

**WARRANTY STATEMENT:**

Information about ROCK-TRED products is given to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you will make your own tests to determine the suitability of the product for your particular purpose. As products are often applied or used under conditions beyond our control, ROCK-TRED cannot guarantee anything but the quality of its products. ROCK-TRED warrants that its products meet the specifications set forth by ROCK-TRED, but we reserve the right to change any given specification without prior notice. ROCK-TRED DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of ROCK-TRED products constitutes acceptance of the terms of this limited warranty and the terms and the conditions set out in our invoice, contrary provisions of buyer's purchase documents notwithstanding. Upon receipt of merchandise, purchaser has 30 days to notify ROCK-TRED in writing that materials are defective. In the event ROCK-TRED finds that the product delivered is off specification, ROCK-TRED will, at its sole discretion, either replace the product or refund the purchase price thereof, and ROCK-TRED's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of ROCK-TRED exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. ROCK-TRED will under no circumstances be liable for special, incidental or consequential damages. This warranty supercedes all other guaranties, whether oral or written, and whether expressed, implied or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals which may cause serious physical injury. Before using, please read the Material Safety Data Sheet and follow all precautions to prevent bodily harm.

THIXO DS REV: 4/03



Manufacturing and Headquarters: 3415 Howard St., Skokie, IL 60076-4032 U.S.A.

(800) ROC-TRED • (800) 762-8733 • (847) 673-8200 • FAX (847) 679-6665

[www.rocktred.com](http://www.rocktred.com)