

Product Description:

CHEM-THANE WB GLOSS V.2013 is a water clear, two-component, water-based aliphatic polyurethane. This unique non-yellowing polyurethane coating produces an exceptionally hard high gloss finish with high level abrasion and stain resistance. **CHEM-THANE WB GLOSS V.2013** remains non-chalking, has superior UV resistance, provides excellent long-lasting protection from many chemicals and offers superior wear through durability while producing no strong odors during application or curing.

CHEM-THANE WB GLOSS V.2013 is an ideal protective finish coat for ROCK-TRED's standard and decorative floor and wall systems. Its high level stain and abrasion resistance makes **CHEM-THANE WB GLOSS V.2013** an excellent finish coat across industries such as pharmaceutical, healthcare, warehousing and manufacturing as well as for use as an anti-graffiti coating. This water based product is easy to apply, environmentally safe and meets all USDA/FDA guidelines for installation in federally inspected facilities

Physical Testing Information:

Volume mix ratio:	1.83: 1 (Resin to Hardener)
Viscosity (mixed):	200-300 CPS Typical
Solids Content (%):	27% (ASTM D-2697)
Hardness:	70 (Shore D)
Stain Resistance	8.0* (ASTM D6578-08) *See ASTM Report
VOC:	11.18 g/l EPA method 24)
Application Temps:	60 ⁰ – 85 ⁰ F (13 ⁰ – 29 ⁰ C)
Gel Time	45 minutes @ 75 ⁰ F
Dry to Touch (recoat with compatible product)	2-3 hours (min.) @ 75 ⁰ F (24 ⁰ C)
Through-Cure	4-6 hours @ 75 ⁰ F (24 ⁰ C)
Open for Light Traffic	12 hours (min.) @ 75 ⁰ F (24 ⁰ C)
Shelf Life	6 months in unopened containers

Please review ROCK-TRED's Product Data Sheet and SDS for further information on this product. All physical testing information is from performance testing run on neat coats of the tested product unless otherwise indicated.